

ffcode: L^AT_EX Package for Fixed-Font Code Blocks*

Yegor Bugayenko
yegor256@gmail.com

2025/01/02, 0.10.0

1 Introduction

This package helps you write source code in your articles and make sure it looks nice. Install it from CTAN and then use like this (pay attention to `\ff` command and `ffcode` environment):

<pre> The function <code>fibonacci()</code> is recursive: 1 <code>int fibonacci(int n) {</code> 2 <code>if (n < 2) {</code> 3 <code>return n;</code> 4 <code>}</code> 5 <code>return fibonacci(n-1)+fibonacci(n-2);</code> 6 <code>}</code> Line no. 3 returns <code>n</code> and terminates it.</pre>	<pre>1 \documentclass{article} 2 \usepackage{ffcode} 3 \pagestyle{empty} 4 \begin{document} 5 The function <code>fibonacci()</code> is recursive: 6 \begin{ffcode} 7 int fibonacci(int n) { 8 if (n < 2) { 9 return n; (*@ \label{ln:ret} @*) 10 } 11 return fibonacci(n-1)+fibonacci(n-2); 12 } 13 \end{ffcode} 14 Line no.~\ref{ln:ret} returns <code>ff{n}</code> 15 and terminates it. 16 \end{document}</pre>
--	---

`\ffinput` There is also `\ffinput` command that reads the content from a file and places it into the document, formatted exactly the same way as it would be, if the `ffcode` environment would be used.

2 Package Options

`samepage` If you want to avoid page breaks inside `ffcode` blocks, use the `samepage` package option.

`noframes` If you want to omit the light gray frames around `\ff` texts, use the package option `noframes`.

*The sources are in GitHub at [yegor256/ffcode](https://github.com/yegor256/ffcode)

- `nobars` To omit the vertical gray bar at the left side of each snippet, use `nobars` option of the package.
- `nonumbers` To omit the line numbers, use `nonumbers` option of the package.
- `nocn` By default, the numbering is continuous: line numbers start at the first snippet and increment until the end of the document. If you want them to start from one at each snippet, use `nocn` (stands for “no continuous numbering”) option of the package.
- `bold` You can make your `\ff` pieces look bolder than usual, which may be pretty convenient for some document classes (pay attention to the usage of the [lmodern](#) package, without it the bold won’t work, as explained [here](#)):

<p>Sometimes it’s necessary to make code pieces look bolder, like the <code>fibonacci</code> function in this text.</p>	<pre> 4 \usepackage{lmodern} 5 \usepackage[bold,noframes]{ffcode} 6 \begin{document} 7 Sometimes it’s necessary to make 8 code pieces look bolder, like 9 the fibonacci function in this text. 10 \end{document} </pre>
---	---

- `sf` You can change the font family of `\ff` pieces to `\sffamily`:

<p>Sometimes you may want them to look not strictly fixed-width, but more elegant, like the <code>fibonacci</code> here.</p>	<pre> 4 \usepackage[sf,bold,noframes]{ffcode} 5 \begin{document} 6 Sometimes you may want them to look 7 not strictly fixed-width, but more 8 elegant, like the \emph{ fibonacci } 9 here. 10 \end{document} </pre>
--	---

3 Typesetting

By the way, the package correctly formats low-height texts, for example, just a dot: `\dot`.
 A pair of vertical lines decorate a TeX command inside the snippet. If you want to print a single vertical line, use this: “`|\char‘\vert|`”.
 The command `\ff` behaves differently in math mode – it doesn’t add gray frames:

$x = \int_{\text{home}}^N f(x).$	<pre> 6 \begin{equation*} 7 x = \int_{\text{home}}^N f(x). 8 \end{equation*} </pre>
----------------------------------	---

4 Line Highlighting

You can highlight some lines in your `ffcode` environment, or can use any other additional configuration parameters from `fancyvrb` and `fvextra` packages:

```

1 while (true) {
2   print("Hi!")
3   print("Enter your name:")
4   scan(x)
5   print("You name | " + x)
6 }

```

```

6 \begin{ffcode}[backgroundcolor=\color{gray!20}]
7 while (true) {
8   (*\textcolor{red}{print("Hi!")})
9   print("Enter your name:")
10  scan(x)
11  print("You name | " + x)
12 }
13 \end{ffcode}

```

Using this second argument of `ffcode`, you can provide any other options from the `listings` package to the snippet.

5 Implementation

First, we parse package options with the help of `pgfopts` package:

```

1 \RequirePackage{pgfopts}
2 \pgfkeys{
3   /ff/.cd,
4   bold/.store in=\ff@bold,
5   sf/.store in=\ff@sf,
6   samepage/.store in=\ff@samepage,
7   noframes/.store in=\ff@noframes,
8   nonumbers/.store in=\ff@nonumbers,
9   nobars/.store in=\ff@nobars,
10  novert/.store in=\ff@novert,
11  nocn/.store in=\ff@nocn,
12 }
13 \ProcessPgfPackageOptions{/ff}

```

Then, we include the `xcolor` package:

```
14 \RequirePackage{xcolor}
```

Then, we configure the `listings` package:

```

15 \RequirePackage{listings}
16 \makeatletter
17 % See \href{https://tex.stackexchange.com/questions/706858}{the explanation}:
18 \lst@AddToHook{Init}{\setlength{\lineskip}{0pt}}
19 \makeatother

```

Then, we define a supplementary command `\ff@set`:

```

20 \makeatletter
21 \newcommand\ff@set[1]{
22   \lstset{breaklines}
23   \lstset{escapeinside={(*@}{@*)}}
24   \lstset{basicstyle={\ttfamily}}
25   \lstset{columns=fullflexible}
26   \ifdefined\ff@nonumbers\else
27     \lstset{numbers=left,numbersep=.8em,numberstyle={\tiny\sffamily\color{gray}}}
28   \fi
29   \ifdefined\ff@nobars\else
30     \lstset{frame=leftline,framerule=.05em,rulecolor={\color{gray}}}
31   \fi
32   \ifdefined\ff@nocn\else

```

```

33 \lstset{firstnumber=last}
34 \fi
35 \lstset{#1}
36 }
37 \makeatother

```

`ffcode` Then, we define the `ffcode` environment and its supplementary `ffcode*` counterpart:

```

38 \makeatletter
39 \lstnewenvironment{ffcode}[1]{}
40 {\ff@set{#1}\ifdefined\ff@samepage\begin{minipage}{\linewidth}\fi}
41 {\ifdefined\ff@samepage\end{minipage}\fi}
42 \makeatother

```

`ffcode` Then, we define the `\ffinput` command:

```

43 \makeatletter
44 \newcommand\ffinput[2][]{%
45 \ff@set{#1}%
46 \ifdefined\ff@samepage\begin{minipage}{\linewidth}\fi%
47 \lstinputlisting[#1]{#2}%
48 \ifdefined\ff@samepage\end{minipage}\fi%
49 }
50 \makeatother

```

`\ff@print` Then, we define a supplementary macro `\ff@print`:

```

51 \makeatletter
52 \newcommand\ff@print[1]{%
53 \textnormal{%
54 \ifdefined\ff@sf\sffamily\else\ttfamily\fi%
55 \ifdefined\ff@bold\fontseries{b}\selectfont\fi%
56 #1%
57 }%
58 }
59 \makeatother

```

`\ff@rule` Then, we define supplementary command `\ff@rule`:

```

60 \makeatletter\newcommand\ff@rule
61 {\vrule height 0.6em depth 0.1em width 0em}
62 \makeatother

```

`tcolorbox` Then, we use `tcolorbox` to define `\ff@box` command for a gray box around verbatim text block:

```

63 \makeatletter
64 \ifdefined\ff@noframes\else
65 \RequirePackage{tcolorbox}
66 \newtcbbox\ff@box{nobeforeafter,colframe=gray!80!white,
67 colback=gray!5!white,boxrule=0.01em,arc=0.1em,
68 boxsep=0.12em,left=0.05em,right=0.05em,top=0.02em,bottom=0.02em,
69 tcbbox raise base}
70 \fi
71 \makeatother

```

`\ff@x` Then, we define `\ff@x` internal command for printing a piece of fixed-width-font text:

```

72 \makeatletter
73 \NewDocumentCommand\ff@x{v}{\ff{#1}}
74 \makeatother

```

`\ff` Then, we define `\ff` macro:

```
75 \makeatletter
76 \newcommand\ff[1]{%
77   \ifdefined\ff@noframes%
78     \ff@rule\ff@print{#1}%
79   \else%
80     \relax\ifmmode%
81       \ff@rule\ff@print{#1}%
82     \else%
83       \ff@box{\ff@rule\ff@print{#1}}%
84     \fi%
85   \fi%
86 }
87 \makeatother
```

`novert` Finally, we let vertical bars work similar to `\ff`, as suggested [here](#) and [here](#) (unless `novert` package option is used):

```
88 \makeatletter\ifdefined\ff@novert\else
89   \catcode'\|\active
90   \AtBeginDocument{\catcode'\|\active\protected\def|\ff@x|}
91   \catcode'\| 12 %
92 \fi\makeatother

93 \endinput
```

Change History

v0.1.0		added, to disable redefinition of vertical bar.	3
	General: Initial version		3
v0.10.0		We use <code>pgfopts</code> instead of <code>xkeyval</code>	3
	General: Package option <code>samepage</code> added, to keep all <code>ffcode</code> blocks on the same page.		3
	<code>ffcode</code> : The <code>\ffinput</code> command added.		4
v0.2.0			
	General: Package options <code>nonumbers</code> and <code>noframes</code> added.		3
v0.3.0			
	General: Package option <code>nocn</code> added.		3
v0.4.0			
	General: Package option <code>nobars</code> added.		3
v0.5.1			
	<code>\ff@print</code> : Now, the command <code>ff</code> ignores italic and bold and always prints <code>\texttt</code> as it should be.		4
v0.6.0			
	General: Package option <code>novert</code>		
		added, to disable redefinition of vertical bar.	3
		We use <code>pgfopts</code> instead of <code>xkeyval</code>	3
	v0.7.0		
		General: Package option <code>bold</code> added, to make all <code>\ff</code> pieces look bolder than usual.	3
		Package option <code>sf</code> added, to make all <code>\ff</code> pieces be printed as <code>\sffamily</code>	3
	v0.8.0		
		<code>\ff</code> : The <code>\ff</code> command is now a normal command, not verbatim.	5
	v0.9.0		
		General: The <code>minted</code> package is replaced by the <code>listings</code> package.	3
	v0.9.2		
		General: All lengths and sizes are in "em" instead of "pt".	3

Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in *roman* refer to the code lines where the entry is used.

Symbols	<code>\ff@samepage</code>	<code>\makeatother</code>
<code>\ </code> <i>89, 90, 91</i> <i>6, 40, 41, 46, 48</i> <i>19, 37, 42, 50,</i> <i>59, 62, 71, 74, 87, 92</i>
A	<code>\ff@set</code> <i>21, 40, 45</i>	N
<code>\active</code> <i>89, 90</i>	<code>\ff@sf</code> <i>5, 54</i>	<code>\NewDocumentCommand</code> . <i>73</i>
<code>\AtBeginDocument</code> . . . <i>90</i>	<code>\ff@x</code> <i>72, 90</i>	<code>\newtcbbox</code> <i>66</i>
B	<code>\ffcode</code> <i>38, 43</i>	<code>\novert</code> <i>88</i>
<code>\begin</code> <i>40, 46</i>	<code>\ffinput</code> <i>44</i>	P
C	<code>\fontseries</code> <i>55</i>	<code>\pgfkeys</code> <i>2</i>
<code>\catcode</code> <i>89, 90, 91</i>	H	<code>\ProcessPgfPackageOptions</code> <i>13</i>
<code>\color</code> <i>27, 30</i>	<code>\href</code> <i>17</i>	<code>\protected</code> <i>90</i>
D	I	R
<code>\def</code> <i>90</i>	<code>\ifdefined</code> <i>26,</i> <i>29, 32, 40, 41, 46,</i> <i>48, 54, 55, 64, 77, 88</i>	<code>\relax</code> <i>80</i>
E	<code>\ifmmode</code> <i>80</i>	<code>\RequirePackage</code> <i>1, 14, 15, 65</i>
<code>\end</code> <i>41, 48</i>	L	S
<code>\endinput</code> <i>93</i>	<code>\lineskip</code> <i>18</i>	<code>\selectfont</code> <i>55</i>
F	<code>\linewidth</code> <i>40, 46</i>	<code>\setlength</code> <i>18</i>
<code>\ff</code> <i>73, 75</i>	<code>\lst@AddToHook</code> <i>18</i>	<code>\sffamily</code> <i>27, 54</i>
<code>\ff@bold</code> <i>4, 55</i>	<code>\lstinputlisting</code> <i>47</i>	T
<code>\ff@box</code> <i>66, 83</i>	<code>\lstnewenvironment</code> . . <i>39</i>	<code>\tcolorbox</code> <i>63</i>
<code>\ff@nobars</code> <i>9, 29</i>	<code>\lstset</code> <i>22, 23,</i> <i>24, 25, 27, 30, 33, 35</i>	<code>\textnormal</code> <i>53</i>
<code>\ff@nocn</code> <i>11, 32</i>	M	<code>\tiny</code> <i>27</i>
<code>\ff@noframes</code> <i>7, 64, 77</i>	<code>\makeatletter</code>	<code>\ttfamily</code> <i>24, 54</i>
<code>\ff@nonumbers</code> <i>8, 26</i> <i>16, 20, 38, 43,</i> <i>51, 60, 63, 72, 75, 88</i>	V
<code>\ff@novert</code> <i>10, 88</i>	V	<code>\vrule</code> <i>61</i>
<code>\ff@print</code> <i>51, 78, 81, 83</i>		
<code>\ff@rule</code> <i>60, 78, 81, 83</i>		