

Bibliography formatting with citation-style-language

Zeping Lee*

2024-06-09 v0.5.0

1 Introduction

The Citation Style Language¹ (CSL) is an XML-based language that defines the formats of citations and bibliography. There are currently thousands of styles in CSL including the most widely used APA, Chicago, Vancouver, etc. The `citation-style-language` package is aimed to provide another reference formatting method for LaTeX that utilizes the CSL styles. It contains a citation processor implemented in pure Lua (`citeproc-lua`) which reads bibliographic metadata and performs sorting and formatting on both citations and bibliography according to the selected CSL style. A LaTeX package (`citation-style-language.sty`) is provided to communicate with the processor.

Note that this project is in early development stage and some features of CSL are not implemented yet. Comments, suggestions, and bug reports are welcome.

2 Installation

This package is available from TeX Live 2022 or later versions. For most users, the easiest way is to install it via `tlmgr`. If you want to install the GitHub develop version of this package, you may follow the steps below.

The `citation-style-language` requires the following packages: `filehook`, `l3kernel`, `l3packages`, `lua-uca`, `lua-luajob`, `luatex`, `luaxml`, and `url`. `l3build` is also required for actually performing the installation. Make sure they are already installed in the TeX distribution.

```
git clone https://github.com/zepinglee/citeproc-lua # Clone the repository
cd citeproc-lua
git submodule update --init --remote # Fetch submodules
l3build install
```

These commands install the package files to `TEXMFHOME` which is usually `~/texmf` on Linux or `~/Library/texmf` on macOS. Besides, the `citeproc-lua` executable needs to be copied to some directory in the `PATH` environmental variable so that it can be called directly in the shell. For example provided `~/bin` is in `PATH`:

```
cp citeproc/citeproc-lua.lua "~/bin/citeproc-lua"
```

To uninstall the package from `TEXMFHOME`, just run `l3build uninstall`.

*E-mail: zepinglee@gmail.com

¹<https://citationstyles.org/>

3 Getting started

An example of using citation-style-language package is as follows.

```
\documentclass{...}
\usepackage[style = apa]{citation-style-language}
\addbibresource{bibfile.json}
\begin{document}
\cite{...}
...
\printbibliography
\end{document}
```

The procedure to compile the document is different across engines.

LuaTeX The CSL processor is written in Lua and it can be run directly in LuaTeX without the need of running external programs. For LuaTeX, the compiling procedure is simply running latex twice, which is the same as documents with cross references.

Other engines For engines other than LuaTeX, the citeproc-lua executable is required to run on the .aux file to generate the citations and bibliography. The general procedure is similar to the traditional BibTeX workflow.

1. Run latex on example.tex.
2. Run citeproc-lua on example.aux. The engine reads the .cs1 style, CSL locale files, and .bib database and then writes the processed citations and bibliography to example.bbl.
3. Run latex on example.tex. The .bbl file is loaded and all the citations and bibliography are printed.

4 Package setup

`\cslsetup` `\cslsetup{<options>}`

Package options may be set when the package is loaded or at any later stage with the `\cslsetup` command. These two methods are equivalent.

```
\usepackage[style = apa]{citation-style-language}
% OR
\usepackage{citation-style-language}
\cslsetup{style = apa}
```

`style` The `style=<style-id>` option selects the style file `<style-id>.cs1` for both citations and bibliography. The implemented CSL style files are available in the official GitHub repository² as well as the Zotero style repository³. The user may search and download the .cs1 file to the working directory. The following styles are distributed within the package and each of them can be directly loaded without downloading.

²<https://github.com/citation-style-language/styles>

³<https://www.zotero.org/styles>

`american-chemical-society` American Chemical Society

`american-medical-association` American Medical Association 11th edition

`american-political-science-association` American Political Science Association

`american-sociological-association` American Sociological Association 6th edition

`apa` American Psychological Association 7th edition

`chicago-author-date` Chicago Manual of Style 17th edition (author-date)

`chicago-fullnote-bibliography` Chicago Manual of Style 17th edition (full note)

`chicago-note-bibliography` Chicago Manual of Style 17th edition (note)

`elsevier-harvard` Elsevier - Harvard (with titles)

`harvard-cite-them-right` Cite Them Right 11th edition - Harvard

`ieee` IEEE

`modern-humanities-research-association` Modern Humanities Research Association 3rd edition (note with bibliography)

`modern-language-association` Modern Language Association 9th edition

`nature` Nature

`vancouver` Vancouver

`locale` The `locale` option receives an ISO 639-1 two-letter language code (e.g., “en”, “zh”), optionally with a two-letter locale code (e.g., “de-DE”, “de-AT”). This option affects sorting of the entries and the output of dates, numbers, and terms (e.g., “et al.”). It may also be set `auto` (default) and the `default-locale` attribute in the CSL style file will be used. The locale falls back to “en” (English) if the attribute is not set. When `babel` package is loaded, the selected main language is implicitly set as the `locale` for `citation-style-language`.

`bib-font` Usually, the list of references is printed in the same font style and size as the main text. The `bib-font` option is used to set different formats in the `thebibliography` environment. It may override the `line-spacing` attribute configured in the CSL style. For example, to force double-spacing in the bibliography:

```
\cslsetup{bib-font = \linespread{2}\selectfont}
```

`bib-item-sep` The vertical space between entries in the bibliography is configured in the CSL style. It can be overridden by this `bib-item-sep` option. It is recommended to set `bib-item-sep` to a stretchable glue rather than a fixed length to help reducing page breaks in the middle of an entry.

```
\cslsetup{bib-item-sep = 8 pt plus 4 pt minus 2 pt}
```

Table 1: The locators supported in CSL v1.0.2.

act	folio	section
appendix	issue	sub-verbo
article	line	supplement
book	note	table
canon	opus	timestamp
chapter	page	title
column	paragraph	verse
elocation	part	version
equation	rule	volume
figure	scene	

`bib-hang` The `bib-hang` option sets the hanging indentation length which is usually used for author-date style references. By default, it is 1 em (with respect to the `bib-font` size if set).

`bib-par-indent` The paragraph indentation of references if they are in normal paragraph style rather than labelled or hanging indented. By default, it is the `\parindent` at when printed out.

`\addbibresource` `\addbibresource{⟨resource⟩}`

The `\addbibresource` command loads bibliographic data from `⟨resource⟩` file. CSL-JSON is the preferred format especially when the data is exported from a reference manager like Zotero. Other formats like CSL-YAML and Bib(La)TeX (for compatibility) are also supported but they need to be converted to CSL-JSON for internal processing. Note that the files must be specified with their extension names and the content should be encoded in UTF-8.

```
\addbibresource{file1.json}
\addbibresource{file2.yaml, file3.bib}
```

5 Citation commands

`\cite` `\cite[⟨options⟩]{⟨keys⟩}`

The citation command is similar to the one in standard LaTeX except that the prefix `⟨options⟩` is in key-value style. The `⟨options⟩` can be `prefix`, `suffix` or one of `locators` like `page` or `figure`. The full list of supported locators is detailed in Table 1. An example is as follows.

```
\cite[prefix = {See }, page = 42]{ITEM-1}
```

The traditional form `\cite[⟨prenote⟩][⟨postnote⟩]{⟨keys⟩}` introduced in `natbib` and `biblatex` is also supported but not recommended. If only one optional argument is provided, it is treated as `⟨postnote⟩`. The `⟨postnote⟩` is used as a page locator if it consists of only digits.

`\parencite` `\parencite[<options>]{<keys>}`
`\citep`

The `\parencite` and `\citep` command are aliases of `\cite`. They are added for compatibility with `biblatex` and `natbib` packages. If the citation format defined in the CSL style does not have affixes, these commands in `citation-style-language` do not enclose the output with brackets, which is different from other packages.

`\textcite` `\textcite[<options>]{<keys>}`
`\citet`

These commands produce narrative in-text citation where the author name is part of the running text followed by the year in parentheses. These commands only work with author-date styles.

`infix` An extra option `infix` can be given to specify the text inserted between the author and year parts. For example, “Keseý’s early work (1962)” can be produced by `\textcite[infix={’s early work}]{ITEM-1}`. By default the infix is a space.

`\footcite` `\footcite[<options>]{<keys>}`

This command is similar to `\cite`. It is for compatibility with `biblatex`.

`\cites` `\cites[<options>]{<key>}...[<options>]{<key>}`

The `\cites` accepts multiple cite items in a single citation. This command scans greedily for arguments and a following bracket may be mistakenly recognized as a delimiter. To prevent this, an explicit `\relax` command is required to terminate the scanning process. The following example illustrates its usage.

```
\cites[prefix = {See }, page = 6]{key1}[section = 2.3]{key2}\relax [Text]
```

`\citeauthor` `\citeauthor{<key>}`

This command prints the author name. If the original citation does not contain the author name (e.g., a numeric style), an optional `<intext>` element can be supplied as a sibling to the `<citation>` and `<bibliography>` elements in the CSL style (see [citeproc’s documentation](#) for details).

`\citeyearpar` `\citeyearpar[<options>]{<keys>}`

This command suppresses the author names in the citation. It is equivalent to `\cite` with `suppress-author` option enabled.

`\fullcite` `\fullcite[<options>]{<keys>}`

This command prints a full citation similar to the bibliographic entry. The contents are generated from the `<bibliography>` element in the CSL style rather than the `<citation>` element.

`\nocite` `\nocite{<keys>}`

This command produces no output but makes the entries included in the bibliography, which is the same in standard L^AT_EX. If the special key `*` is given (`\notecite{*}`), all the entries in the database are included.

6 Bibliography commands

`\printbibliography` `\printbibliography`
`\printbibliography[options]`

This command prints the reference list. It also accepts an optional argument in square brackets which is a list of key-value options. The following options are available.

`heading` `heading = name`

This option selects the section heading style defined with `\defbibheading`. The default heading for `\printbibliography` is `bibliography`.

`title` `title = text`

This option sets the title in the heading.

`label` `label = label`

This option is equivalent to `\label{label}` after the heading so that it can be `\refed` from other parts in the document.

`prenote` `prenote = name`
`postnote` `postnote = name`

`type` `type = entrytype`

Print only the entries of the given `entrytype`. Note that the `entrytype` should be the name of a CSL entry type rather than BibTeX entry type (e.g., use `article-journal` rather than `article`).

`notype` `notype = entrytype`

Print only the entries that are not `entrycategory`. This option may be used multiple times.

`keyword` `keyword = keyword`

Print only the entries whose keyword field includes the given `keyword`. This option may be used multiple times.

`notkeyword` `notkeyword = keyword`

Print only the entries whose keyword field does not include the given $\langle keyword \rangle$. This option may be used multiple times.

`category` `category = $\langle category \rangle$`

Print only the entries assigned to the given category. This option may be used multiple times.

`notcategory` `notcategory = $\langle category \rangle$`

Print only the entries assigned to the given category. This option may be used multiple times.

6.1 Bibliography Headings

`\defbibheading` `\defbibheading $\langle name \rangle$ [$\langle title \rangle$][$\langle code \rangle$]`

This command defines a bibliographic heading which can be used with the `bibheading` option of `\printbibliography`. The $\langle name \rangle$ is an identifier assigned to the defined style. If a `title` option is given in the `\printbibliography`, it is passed to the code as `#1`. Otherwise the value $\langle title \rangle$ in the optional argument is used by default. The following is the definition of the default heading when used in a book class.

```
\defbibheading{bibliography}{\bibname}{%
  \chapter*{#1}%
  \markboth{\MakeUppercase{#1}}{\MakeUppercase{#1}}%
}
```

The following are predefined headings which can be used directly.

bibliography The default heading used by `\printbibliography`.

subbibliography Similar to `bibliography` but one sectioning level lower.

bibintoc Similar to `bibliography` but adds an entry to the table of contents.

subbibintoc Similar to `subbibliography` but adds an entry to the table of contents.

bibnumbered Similar to `bibliography` but uses `\chapter` or `\section` to create a numbered heading which is also added to the table of contents.

subbibnumbered Similar to `subbibliography` but uses `\chapter` or `\section` to create a numbered heading which is also added to the table of contents.

none An empty heading.

7 Compatibility with other packages

babel The main language set by `babel` is used as the locale for `citation-style-language`. In general, `babel` is supposed to be loaded before `citation-style-language`.

beamer Most of this package's features work fine with **beamer** except the `backref` option. At the moment this can be addressed with `hyperref`'s `backref` option.

hyperref When `hyperref` is loaded, the DOIs, PMIDs, and PMCIDs are correctly rendered as hyperlinks.

Incompatible packages The following packages are not compatible with `citation-style-language`. An error will be triggered if any of them is loaded together with `citation-style-language`.

- `babelbib`
- `backref`
- `biblatex`
- `bibtopic`
- `bibunits`
- `chapterbib`
- `cite`
- `citeref`
- `inlinebib`
- `jurabib`
- `mcite`
- `mciteplus`
- `multibib`
- `natbib`
- `splitbib`